

Find us on



Magnus

Inclined
Monocular
Microscope

MLX-M Plus

Key Features

- Anti-fungus treatment
- Easy access for lamp replacement
- Choice of halogen and LED illumination
- Parfocal and centered stain free optics
- Optics with multi-layer coating and anti-fungus treated



www.magnusopto.com

SPECIFICATIONS

Magnus Inclined Monocular Microscope

Item	Specifications	MLX-M Plus Monocular (SP)										
Optical System	Semi-Plan (SP) optics	✓										
Body	Aluminium Die- cast body based on ball bearing and wire guides thereby ensuring smooth and precise manipulation.	✓										
Inclined Observation Head	Monocular 30 degree inclined, rotatable through 360 degrees	✓										
Eyepiece (widefield) For Observation	HWF 10x (FN 18mm) eyepiece. The unique optical design of the compensating eyepiece provides relief from eye fatigue and renders color-compensated wide-field images of utmost clarity.	✓										
Nosepiece	Quadruple revolving nosepiece based on precision ball-bearing mechanism with positive stop click	✓										
Objectives	<table border="0"> <tr> <td>Semi- Plan Achromat Objectives</td> <td>NA</td> </tr> <tr> <td>SP 4x</td> <td>0.10</td> </tr> <tr> <td>SP 10x</td> <td>0.25</td> </tr> <tr> <td>SP 40x (spring loaded)</td> <td>0.65</td> </tr> <tr> <td>SP 100x (oil, spring loaded)</td> <td>1.25</td> </tr> </table> Uniformly centered, interchangeable & parfocal Anti-fungus treated	Semi- Plan Achromat Objectives	NA	SP 4x	0.10	SP 10x	0.25	SP 40x (spring loaded)	0.65	SP 100x (oil, spring loaded)	1.25	✓
Semi- Plan Achromat Objectives	NA											
SP 4x	0.10											
SP 10x	0.25											
SP 40x (spring loaded)	0.65											
SP 100x (oil, spring loaded)	1.25											
Mechanical Stage	Co-axial low drive mechanical stage (125mm x 145mm) (+/-5mm) with traverse area of 50mm x 76mm (+/-5mm)	✓										
Condenser Holder	Rack and pinion mounted condenser holder	✓										
Condenser	Abbe condenser with aperture iris diaphragm (N.A. 1.25) focusable with rack & pinion and a continuously variable iris diaphragm with a removable blue for daylight observation	✓										
Focusing System	Co-axial coarse and fine controls with a focus adjustment and fine adjustment knobs. Coarse focus range 20mm	✓										
Illumination	a) Halogen Lamp OR LED b) LED with battery backup	✓										
Packed in a styrofoam box, with operation manual, dust cover, power chord & immersion oil (5ml). The reflector mirror, spare bulb & wooden cabinet are optionally available.												



Authorised Stockist :

SRI VAISHNAV SCIENTIFIC & LAB EQUIPMENTS

Address: #16-2-749/6 & 6A, Flat no. 105 Sri Tirumala Towers, Revenue Board Colony, Gaddiannaram, Dilsukhnagar, Hyderabad – 36.

Phone :+91 9346001333 , +91 9676491333, E-mail: srivaishnavsle@yahoo.com